

DESCRIPTION

Poltix Paraffin wax solution is an additive for unsaturated polyester materials.

PRINCIPAL CHARACTERISTICS

- Suitable for every polyester gelcoat;
- Addition of Poltix Paraffin wax solution to gelcoats will result in a tack-free surface;
- In almost all applications a dosage of 2% will be sufficient.

COLOURS AND GLOSS

Colourless

BASIS PROPERTIES (AT 23 °C AND 50% R.H.)

Density	:	approx. 0,9 g/cm ³
Solid content	:	approx. 3% (volume)
Recommended dosage	:	approx. 2,0 to 3,0 % by weight
Shelf life	:	separate components, stored cool and dry in original packaging minimum 12 months
Flash point (DIN53213)	:	32 °C

SPREADING RATE

Depending on application : approx. 20 - 30 g/kg polyester material

INSTRUCTIONS FOR USE

BEFORE USE, MIX THOROUGHLY.

Mixing ratio : use 2,0 to 3,0 % by weight.
The actual quantity depends on colour, temperature and application.

ADDITIONAL INFORMATION

- Adding Poltix Paraffin wax solution
Add Poltix Paraffin wax solution slowly to the gelcoat during stirring. Mix thoroughly until homogenous.

SAFETY INFORMATION

This product contains solvents. Take all necessary safety measurements when using this product and arrange proper ventilation and safety equipment for all personnel. For details on safety and health see our material safety data sheet.

Date: September '14
286-99999

Disclaimer

Although the information and recommendations are presented in good faith and believed to be correct at date of issue, De IJssel Coatings B.V. makes no representations as of the completeness or accuracy thereof. In no event De IJssel Coatings B.V. will be responsible for damages of any nature whatsoever resulting from the use of this information.