

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 12

Revision: 23.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Poltix Gelcoat iso/npg airless**

Article number: 216

UFI: MQY4-N06K-700E-PKYM

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU19 Building and construction work

Process category PROC19 Manual activities involving hand contact

Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

AC13 Plastic articles

Article category Dye

Technical function

Application of the substance / the mixture See our technical datasheet for application details of this product.
Gelcoat
Polyester resin

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
Office hours: working days from 08:00 to 17:00 hrs.


SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

 GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

 GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

 GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

styrene

maleic anhydride

Reactionmass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacat and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacat

cobalt(II) 2-ethylhexanoate

Hazard statements

H226 Flammable liquid and vapour.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.03.2021

Version number 12

Revision: 23.03.2021

Trade name: Poltix Gelcoat iso/npg airless

(Contd. of page 1)

<ul style="list-style-type: none"> · Precautionary statements · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: · vPvB: 	<p>H315 Causes skin irritation. H319 Causes serious eye irritation. H317 May cause an allergic skin reaction. H361d Suspected of damaging the unborn child. H335 May cause respiratory irritation. H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation. H412 Harmful to aquatic life with long lasting effects.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p> <p>Not applicable. Not applicable.</p>
---	--

* SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32	styrene ⚠ Flam. Liq. 3, H226; ⚠ Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	25 – 50%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide ⚠ Carc. 2, H351	2.5 – 10%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	1 – 2.5%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40	Reactionmass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacat and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacat ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1A, H317	0.1 – 0.5%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-21195-24678-29	cobalt(II) 2-ethylhexanoate ⚠ Repr. 1A, H360Fd; ⚠ Aquatic Acute 1, H400; ⚠ Eye Irrit. 2, H319; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	0.1 – 0.5%
CAS: 108-31-6 EINECS: 203-571-6 Index number: 607-096-00-9 Reg.nr.: 01-2119472428-31	maleic anhydride ⚠ Resp. Sens. 1, H334; STOT RE 1, H372; ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≤ 0.1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

<ul style="list-style-type: none"> · General information: · After inhalation: · After skin contact: · After eye contact: 	<p>Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.</p> <p>Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.</p> <p>Immediately wash with water and soap and rinse thoroughly.</p> <p>Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.</p>
--	--

(Contd. on page 3)

Trade name: Poltix Gelcoat iso/npg airless

(Contd. of page 2)

- After swallowing: If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- Suitable extinguishing agents: CO2 or powder. Fight larger fires with alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage: No special requirements.
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 4)

Trade name: **Poltix Gelcoat iso/npg airless**

(Contd. of page 3)

*** SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

- Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

IOELV	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm
-------	--

· DNEL (Derived No Effect Level) for workers

100-42-5 styrene

Dermal	Long-term - systemic effects, worker	406 mg/kg bw/day (Worker)
Inhalative	Acute - systemic effects, worker	289 mg/m ³ (Worker)
	Acute - local effects, worker	306 mg/m ³ (Worker)
	Long-term - systemic effects, worker	85 mg/m ³ (Worker)

13463-67-7 titanium dioxide

Inhalative	Long-term - local effects, worker	10 mg/m ³ (Worker)
------------	-----------------------------------	-------------------------------

141-78-6 ethyl acetate

Dermal	Long-term - systemic effects, worker	63 mg/kg bw/day (Worker)
Inhalative	Acute - systemic effects, worker	1468 mg/m ³ (Worker)
	Acute - local effects, worker	1468 mg/m ³ (Worker)
	Long-term - systemic effects, worker	34 mg/m ³ (Worker)
	Long-term - local effects, worker	734 mg/m ³ (Worker)

Reactionmass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacat and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacat

Dermal	Acute - systemic effects, worker	2.5 mg/kg bw/day (Worker)
Inhalative	Acute - systemic effects, worker	2.35 mg/m ³ (Worker)
	Long-term - systemic effects, worker	2.35 mg/m ³ (Worker)

136-52-7 cobalt(II) 2-ethylhexanoate

Inhalative	Long-term - local effects, worker	0.235 mg/m ³ (Worker)
------------	-----------------------------------	----------------------------------

108-31-6 maleic anhydride

Dermal	Acute - systemic effects, worker	0.04 mg/kg bw/day (Worker)
	Acute - local effects, worker	0.04 µg/cm ² (Worker)
	Long-term - systemic effects, worker	0.04 mg/kg bw/day (Worker)
	Long term - local effects, worker	0.04 µg/cm ² (Worker)
Inhalative	Acute - systemic effects, worker	0.8 mg/m ³ (Worker)
	Acute - local effects, worker	0.8 mg/m ³ (Worker)
	Long-term - systemic effects, worker	0.4 mg/m ³ (Worker)
	Long-term - local effects, worker	0.4 mg/m ³ (Worker)

· DNEL (Derived No Effect Level) for the general population

100-42-5 styrene

Oral	Long-term - systemic effects, general population	2.1 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	343 mg/kg bw/day (General population)
Inhalative	Acute - systemic effects, general population	174.25 mg/m ³ (General population)
	Acute - local effects, general population	182.75 mg/m ³ (General population)
	Long-term - systemic effects, general population	10.2 mg/m ³ (General population)

13463-67-7 titanium dioxide

Oral	Long-term - systemic effects, general population	700 mg/kg bw/day (General population)
------	--	---------------------------------------

141-78-6 ethyl acetate

Oral	Long-term - systemic effects, general population	4.5 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	37 mg/kg bw/day (General population)
Inhalative	Acute - systemic effects, general population	734 mg/m ³ (General population)
	Acute - local effects, general population	734 mg/m ³ (General population)

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.03.2021

Version number 12

Revision: 23.03.2021

Trade name: Poltix Gelcoat iso/npg airless

(Contd. of page 4)

	Long-term - systemic effects, general population	367 mg/m ³ (General population)
	Long-term - local effects, general population	367 mg/m ³ (General population)
Reactionmass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacat and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacat		
Oral	Acute - systemic effects, general population	1.25 mg/kg bw/day (General population)
	Long-term - systemic effects, general population	1.25 mg/kg bw/day (General population)
Dermal	Acute - systemic effects, general population	1.25 mg/kg bw/day (General population)
	Long-term - systemic effects, general population	1.25 mg/kg bw/day (General population)
Inhalative	Acute - systemic effects, general population	0.58 mg/m ³ (General population)
	Long-term - systemic effects, general population	0.58 mg/m ³ (General population)
136-52-7 cobalt(II) 2-ethylhexanoate		
Oral	Long-term - systemic effects, general population	0.0558 mg/kg bw/day (General population)
Inhalative	Long-term - local effects, general population	0.037 mg/m ³ (General population)
· PNEC (Predicted No Effect Concentration) values		
100-42-5 styrene		
Aquatic compartment - freshwater		0.028 mg/l (Sediment freshwater)
Aquatic compartment - marine water		0.0028 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		0.04 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater		0.0614 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.0614 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		0.2 mg/kg dw (Soil)
Sewage treatment plant		5 mg/l (stp)
13463-67-7 titanium dioxide		
Aquatic compartment - freshwater		0.127 mg/l (Freshwater)
Aquatic compartment - marine water		1 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		0.61 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater		1000 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		100 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		100 mg/kg dw (Soil)
Oral secondary poisoning		1667 mg/kg food (Food sec poisoning)
141-78-6 ethyl acetate		
Aquatic compartment - freshwater		0.26 mg/l (Freshwater)
Aquatic compartment - marine water		0.026 mg/l (Marine water)
Aquatic compartment - sediment in freshwater		0.34 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.034 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		0.22 mg/kg dw (Soil)
Sewage treatment plant		650 mg/l (stp)
Reactionmass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacat and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacat		
Aquatic compartment - freshwater		0.0022 mg/l (Freshwater)
Aquatic compartment - marine water		0.00022 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		0.009 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater		1.05 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.11 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		0.21 mg/kg dw (Soil)
Sewage treatment plant		1 mg/l (stp)
136-52-7 cobalt(II) 2-ethylhexanoate		
Aquatic compartment - freshwater		0.00149 mg/l (Freshwater)
Aquatic compartment - marine water		0.0069 mg/l (Marine water) ((Co))
Aquatic compartment - sediment in freshwater		27.8 mg/kg sed dw (Sediment freshwater) ((Co))
Aquatic compartment - sediment in marine water		17.8 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		23.1 mg/kg dw (Soil) ((CoH))
Sewage treatment plant		1.08 mg/l (stp) ((Co))

(Contd. on page 6)

Trade name: Poltix Gelcoat iso/npg airless

(Contd. of page 5)

108-31-6 maleic anhydride	
Aquatic compartment - freshwater	0.04281 mg/l (Freshwater)
Aquatic compartment - marine water	0.004281 mg/l (Marine water)
Aquatic compartment - water, intermittent releases	0.4281 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	0.334 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.0334 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	0.0415 mg/kg dw (Soil)
· Additional information:	The lists valid during the making were used as basis.
· 8.2 Exposure controls	
· Personal protective equipment:	
· General protective and hygienic measures:	Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.
· Respiratory protection:	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
· Protection of hands:	Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· Material of gloves	Butyl rubber, BR Fluorocarbon rubber (Viton) The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Recommended thickness of the material: ≥ 0.3 mm
· Penetration time of glove material	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
· For the permanent contact gloves made of the following materials are suitable:	Butyl rubber, BR Fluorocarbon rubber (Viton)
· As protection from splashes gloves made of the following materials are suitable:	Nitrile rubber, NBR
· Not suitable are gloves made of the following materials:	Leather gloves Strong material gloves
· Eye protection:	Tightly sealed goggles

*** SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Viscous
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value at 20 °C:	7
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	145 °C

(Contd. on page 7)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 12

Revision: 23.03.2021

Trade name: Poltix Gelcoat iso/npg airless

(Contd. of page 6)

· Flash point:	31 °C (DIN 51758)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	480 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
· Vapour pressure at 20 °C:	6 hPa
· Density at 20 °C:	1.167 g/cm ³ (DIN 51757, ASTM D 1298)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	1600 – 2000 mPas (Brookfield, ASTM D1544)
Kinematic at 40 °C:	1300 – 1650 mm ² /s
· Solvent content:	
Organic solvents:	35.9 %
VOC (2004/42/EC):	35.92 %
Solids content:	63.3 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

* SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
100-42-5 styrene			
Oral	LD50	5000 mg/kg	(Rat)
13463-67-7 titanium dioxide			
Oral	LD50	> 20000 mg/kg	(Rat)
Dermal	LD50	> 10000 mg/kg	(Rabbit)
141-78-6 ethyl acetate			
Oral	LD50	5620 mg/kg	(Rabbit)

(Contd. on page 8)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 12

Revision: 23.03.2021

Trade name: Poltix Gelcoat iso/npg airless

(Contd. of page 7)

108-31-6 maleic anhydride		
Oral	LD50	400 mg/kg (Rat)
Dermal	LD50	2620 mg/kg (Rabbit)
<ul style="list-style-type: none"> · Primary irritant effect: · Skin corrosion/irritation Causes skin irritation. · Serious eye damage/irritation Causes serious eye irritation. · Respiratory or skin sensitisation May cause an allergic skin reaction. · Additional toxicological information: · CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction) · Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Suspected of damaging the unborn child. · STOT-single exposure May cause respiratory irritation. · STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation. · Aspiration hazard Based on available data, the classification criteria are not met. 		

*** SECTION 12: Ecological information**

<ul style="list-style-type: none"> · 12.1 Toxicity · Aquatic toxicity: No further relevant information available. 			
· Type of test	Effective concentration	Method	Assessment
100-42-5 styrene			
Oral	EC50	5.1 mg/l (Daphnia magna)	
Inhalative	LC50/4 h	24 mg/l (Rat)	
	LC50/96 h	25 mg/l (Lepomis macrochirus)	
141-78-6 ethyl acetate			
Inhalative	LC50/4 h	1600 mg/l (Rat)	
108-31-6 maleic anhydride			
Oral	EC50	84 mg/l (Daphnia magna)	
Inhalative	LC50/96 h	29 mg/l (Desmodesmus subspicatus)	
		138 mg/l (Lepomis macrochirus)	
<ul style="list-style-type: none"> · 12.2 Persistence and degradability No further relevant information available. · 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available. · Ecotoxicological effects: · Remark: Harmful to fish · Additional ecological information: · General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms · 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. · 12.6 Other adverse effects No further relevant information available. 			

*** SECTION 13: Disposal considerations**

<ul style="list-style-type: none"> · 13.1 Waste treatment methods · Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system. 	
· European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage

(Contd. on page 9)

Trade name: Poltix Gelcoat iso/npg airless

(Contd. of page 8)

HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic
HP10	Toxic for reproduction
HP14	Ecotoxic

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1866
· 14.2 UN proper shipping name · ADR/RID/ADN · IMDG, IATA	1866 RESIN SOLUTION RESIN SOLUTION
· 14.3 Transport hazard class(es) · ADR/RID/ADN · Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA · Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number:	Warning: Flammable liquids. 30 F-E,S-E
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information: · ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code · Remarks:	3 D/E In packsize up to 450 liter exempt from ADR according ADR 2.2.3.1.5.
· IMDG · Remarks:	In packaging up to 30 litres exempt according to IMDG 2.3.2.5.
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

*** SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I
None of the ingredients is listed.
- Seveso category
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50000 t

(Contd. on page 10)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 12

Revision: 23.03.2021

Trade name: Poltix Gelcoat iso/npg airless

(Contd. of page 9)

- REGULATION (EC) No 1907/2006
ANNEX XVII

Conditions of restriction: 3

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- National regulations:
- Technical instructions (air):

Class	Share in %
NK	35.9

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360Fd	May damage fertility. Suspected of damaging the unborn child.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

- Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	On basis of test data
Skin corrosion/irritation Serious eye damage/eye irritation Skin sensitisation Reproductive toxicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- Department issuing SDS:
- Contact:
- Abbreviations and acronyms:

Research and Development

Saïda El Asjadi, tel: +31 182 372177, e-mail: safety@de-ijsjel-coatings.nl

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

(Contd. on page 11)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 12

Revision: 23.03.2021

Trade name: Poltix Gelcoat iso/npg airless

(Contd. of page 10)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Carc. 2: Carcinogenicity – Category 2
Repr. 1A: Reproductive toxicity – Category 1A
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Literature data and/or investigation reports are available through the manufacturer.

- Sources:
- * Data compared to the previous version altered.