

05.08.2020

**Kit components**

Product code	Description
--------------	-------------

<b>266</b>	<b>Poltix Vezelplamuur A+B</b>
------------	--------------------------------

Components:

265	Poltix Vezelplamuur
-----	---------------------

290	PEROXAN BP-PASTE 50 PF
-----	------------------------

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

Trade name: **Poltix Vezelplamuur**

Article number: 265

UFI: VAF2-J014-K00K-RWXQ

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites  
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

SU19 Building and construction work

Product category PC9b Fillers, putties, plasters, modelling clay

Process category PROC19 Manual activities involving hand contact

Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

Article category AC13 Plastic articles

Application of the substance / the mixture See our technical datasheet for application details of this product.  
 Filler and surfacer

**1.3 Details of the supplier of the safety data sheet**

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht  
 Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.


**1.4 Emergency telephone number:**

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl  
 Office hours: working days from 08:00 to 17:00 hrs.


**SECTION 2: Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008

 GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

 GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

 GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

    
 GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling: styrene

Hazard statements H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 34

Revision: 17.12.2019

**Trade name: Poltix Vezelplamuur**

(Contd. of page 1)

- Precautionary statements
  - H372 Causes damage to the hearing organs through prolonged or repeated exposure.  
Route of exposure: Inhalation.
  - H412 Harmful to aquatic life with long lasting effects.
  - P101 If medical advice is needed, have product container or label at hand.
  - P102 Keep out of reach of children.
  - P103 Read label before use.
  - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
  - P260 Do not breathe dust/fume/gas/mist/vapours/spray.
  - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
  - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - P405 Store locked up.
  - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

#### · 3.2 Chemical characterisation: Mixtures

- Description: Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

CAS: 100-42-5	styrene	25 – 50%
EINECS: 202-851-5	⚠ Flam. Liq. 3, H226; ⚠ Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304;	
Index number: 601-026-00-0	⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335;	
Reg.nr.: 01-2119457861-32	Aquatic Chronic 3, H412	

- Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### · 4.1 Description of first aid measures

- General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

#### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### · 5.1 Extinguishing media

- Suitable extinguishing agents: CO2 or powder. Fight larger fires with alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet

#### · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

#### · 5.3 Advice for firefighters

- Protective equipment: Mouth respiratory protective device.

(Contd. on page 3)

Trade name: **Poltix Vezelplamuur**

(Contd. of page 2)

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
 Mount respiratory protective device.  
 Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
 Do not allow product to reach sewage system or any water course.  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
 Dispose contaminated material as waste according to item 13.  
 Ensure adequate ventilation.
- **6.4 Reference to other sections**  
 See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.  
 Prevent formation of aerosols.
- Information about fire - and explosion protection:  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:  
 Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:  
 Recommended storage temperature: Keep container tightly sealed.  
 5 - 30 °C
- **7.3 Specific end use(s)**  
 No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- Additional information about design of technical facilities: No further data; see item 7.
- **8.1 Control parameters**
- Ingredients with limit values that require monitoring at the workplace:  
 The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNEL (Derived No Effect Level) for workers		
<b>100-42-5 styrene</b>		
Dermal	Long-term - systemic effects, worker	406 mg/kg bw/day (Worker)
Inhalative	Acute - systemic effects, worker	289 mg/m <sup>3</sup> (Worker)
	Acute - local effects, worker	306 mg/m <sup>3</sup> (Worker)
	Long-term - systemic effects, worker	85 mg/m <sup>3</sup> (Worker)
· DNEL (Derived No Effect Level) for the general population		
<b>100-42-5 styrene</b>		
Oral	Long-term - systemic effects, general population	2.1 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	343 mg/kg bw/day (General population)
Inhalative	Acute - systemic effects, general population	174.25 mg/m <sup>3</sup> (General population)

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 05.08.2020

Version number 34

Revision: 17.12.2019

**Trade name: Poltix Vezelplamuur**

(Contd. of page 3)

Acute - local effects, general population	182.75 mg/m <sup>3</sup> (General population)
Long-term - systemic effects, general population	10.2 mg/m <sup>3</sup> (General population)

· PNEC (Predicted No Effect Concentration) values

<b>100-42-5 styrene</b>	
Aquatic compartment - freshwater	0.028 mg/l (Sediment freshwater)
Aquatic compartment - marine water	0.0028 mg/l (Marine water)
Aquatic compartment - water, intermittent releases	0.04 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	0.0614 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.0614 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	0.2 mg/kg dw (Soil)
Sewage treatment plant	5 mg/l (stp)

· Additional information: The lists valid during the making were used as basis.

**8.2 Exposure controls**

· Personal protective equipment:  
· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

· Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands: Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves Butyl rubber, BR  
Fluorocarbon rubber (Viton)  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material Recommended thickness of the material:  $\geq 0.3$  mm  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.  
For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

· For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR  
Fluorocarbon rubber (Viton)

· As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR

· Not suitable are gloves made of the following materials: Leather gloves  
Strong material gloves

· Eye protection: Tightly sealed goggles

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

· General Information

· Appearance:

Form: Fluid  
Colour: According to product specification  
· Odour: Characteristic  
· Odour threshold: Not determined.

(Contd. on page 5)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 34

Revision: 17.12.2019

**Trade name: Poltix Vezelplamuur**

(Contd. of page 4)

· pH-value at 20 °C:	7
· Change in condition Melting point/freezing point: Initial boiling point and boiling range:	Undetermined. 145 °C
· Flash point:	31 °C (Pensky Martens, ASTM D93)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	480 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	1.2 Vol % 8.9 Vol %
· Vapour pressure at 20 °C:	6 hPa
· Density at 20 °C: · Relative density · Vapour density · Evaporation rate	1.248 g/cm <sup>3</sup> (DIN 51757, ASTM D 1298) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents: VOC (2004/42/EC):	33.5 % 33.46 %
· Solids content:	66.5 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
<b>100-42-5 styrene</b>			
Oral	LD50	5,000 mg/kg	(Rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 6)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 34

Revision: 17.12.2019

**Trade name: Poltix Vezelplamuur**

(Contd. of page 5)

- CMR effects (carcinogeny, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging the unborn child.
- STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.
- Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.

Type of test	Effective concentration	Method	Assessment
<b>100-42-5 styrene</b>			
Oral	EC50	5.1 mg/l (Daphnia magna)	
Inhalative	LC50/4 h	24 mg/l (Rat)	
	LC50/96 h	25 mg/l (Lepomis macrochirus)	

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Ecotoxicological effects:
- Remark: Harmful to fish
- Additional ecological information:
- General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP10	Toxic for reproduction
HP14	Ecotoxic

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

### SECTION 14: Transport information

· <b>14.1 UN-Number</b>	
· ADR/RID/ADN, IMDG, IATA	UN3269
· <b>14.2 UN proper shipping name</b>	
· ADR/RID/ADN	3269 POLYESTER RESIN KIT mixture
· IMDG, IATA	POLYESTER RESIN KIT mixture

(Contd. on page 7)

Trade name: **Poltix Vezelplamuur**

(Contd. of page 6)

<b>· 14.3 Transport hazard class(es)</b>	
· ADR/RID/ADN	
· Class	3 (FT3) Flammable liquids.
· Label	3
-----	
· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
<b>· 14.4 Packing group</b>	
· ADR/RID/ADN, IMDG, IATA	III
<b>· 14.5 Environmental hazards:</b>	
· Marine pollutant:	No
<b>· 14.6 Special precautions for user</b>	
· Hazard identification number (Kemler code):	Warning: Flammable liquids.
· EMS Number:	-
· Stowage Category	F-E,S-D A
<b>· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	
Not applicable.	
· Transport/Additional information:	
-----	
· ADR/RID/ADN	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: See
· Transport category	3
· Tunnel restriction code	E
· Remarks:	In packsize up to 450 liter exempt from ADR according ADR 2.2.3.1.5.
-----	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: See SP340
· Remarks:	In packaging up to 30 litres exempt according to IMDG 2.3.2.5.
· UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT MIXTURE, 3, III

### SECTION 15: Regulatory information

#### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- National regulations:
- Technical instructions (air):

Class	Share in %
NK	33.5

#### · 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

(Contd. on page 8)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 34

Revision: 17.12.2019

**Trade name: Poltix Vezelplamuur**

(Contd. of page 7)

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
  - H226 Flammable liquid and vapour.
  - H304 May be fatal if swallowed and enters airways.
  - H315 Causes skin irritation.
  - H319 Causes serious eye irritation.
  - H332 Harmful if inhaled.
  - H335 May cause respiratory irritation.
  - H361d Suspected of damaging the unborn child.
  - H372 Causes damage to the hearing organs through prolonged or repeated exposure.  
Route of exposure: Inhalation.
  - H412 Harmful to aquatic life with long lasting effects.
- Classification according to Regulation (EC) No 1272/2008
 

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	On basis of test data
Skin corrosion/irritation Serious eye damage/eye irritation Reproductive toxicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- Department issuing SDS: Research and Development
- Contact: Herman van den Berg, tel: +31 182 372177, e-mail: [safety@de-ijssel-coatings.nl](mailto:safety@de-ijssel-coatings.nl)
- Abbreviations and acronyms:
  - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
  - ICAO: International Civil Aviation Organisation
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
  - IMDG: International Maritime Code for Dangerous Goods
  - IATA: International Air Transport Association
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
  - EINECS: European Inventory of Existing Commercial Chemical Substances
  - ELINCS: European List of Notified Chemical Substances
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)
  - VOC: Volatile Organic Compounds (USA, EU)
  - DNEL: Derived No-Effect Level (REACH)
  - PNEC: Predicted No-Effect Concentration (REACH)
  - LC50: Lethal concentration, 50 percent
  - LD50: Lethal dose, 50 percent
  - PBT: Persistent, Bioaccumulative and Toxic
  - vPvB: very Persistent and very Bioaccumulative
  - Flam. Liq. 3: Flammable liquids – Category 3
  - Acute Tox. 4: Acute toxicity - inhalation – Category 4
  - Skin Irrit. 2: Skin corrosion/irritation – Category 2
  - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
  - Repr. 2: Reproductive toxicity – Category 2
  - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
  - STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
  - Asp. Tox. 1: Aspiration hazard – Category 1
  - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
- Sources: Literature data and/or investigation reports are available through the manufacturer.
- \* Data compared to the previous version altered.

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 57

Revision: 05.08.2020

**\* SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**· 1.1 Product identifier**

· Trade name: PEROXAN BP-PASTE 50 PF

· Article number: 290

· UFI: YCC0-D0HM-Q00Y-0GTV

**· 1.2 Relevant identified uses of the substance or mixture and uses advised against**

· Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites  
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU19 Building and construction work

· Product category PC9b Fillers, putties, plasters, modelling clay

· Process category PROC19 Manual activities involving hand contact

· Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· Article category AC13 Plastic articles

· Application of the substance / the mixture

See our technical datasheet for application details of this product.  
Catalyst

**· 1.3 Details of the supplier of the safety data sheet**

· Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht  
Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

· Further information obtainable from:

Research and Development.


**· 1.4 Emergency telephone number:**

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl  
Office hours: working days from 08:00 to 17:00 hrs.


**SECTION 2: Hazards identification**

**· 2.1 Classification of the substance or mixture**

· Classification according to Regulation (EC) No 1272/2008

 GHS02 flame

Org. Perox. E H242 Heating may cause a fire.

 GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

 GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

**· 2.2 Label elements**

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms

    
GHS02 GHS07 GHS09

· Signal word

Warning

· Hazard-determining components of labelling:

dibenzoyl peroxide

· Hazard statements

H242 Heating may cause a fire.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

P103

Read label before use.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing mist/vapours/spray.

(Contd. on page 2)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 57

Revision: 05.08.2020

**Trade name: PEROXAN BP-PASTE 50 PF**

(Contd. of page 1)

P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P410 Protect from sunlight.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· 2.3 Other hazards**

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients****· 3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

**· Dangerous components:**

CAS: 94-36-0 EINECS: 202-327-6 Index number: 617-008-00-0 Reg.nr.: 01-2119511472-50	dibenzoyl peroxide ⚠ Org. Perox. B, H241; ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	25 – 50%
CAS: 670241-72-2 ELINCS: 447-010-5 Reg.nr.: 01-00000018876-55	isononylbenzoaat ⚠ Aquatic Chronic 2, H411	10 – 25%
CAS: 9038-95-3 EC number: 618-542-7	polyalkylglycolmonobutylether ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	1 – 2.5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****· 4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

**· 4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**· 4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****· 5.1 Extinguishing media**

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

**· 5.2 Special hazards arising from the substance or mixture**

No further relevant information available.

**· 5.3 Advice for firefighters**

- Protective equipment: No special measures required.

**SECTION 6: Accidental release measures****· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**· 6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 57

Revision: 05.08.2020

**Trade name: PEROXAN BP-PASTE 50 PF**

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
  - Keep receptacles tightly sealed.
  - Store in cool, dry place in tightly closed receptacles.
  - Keep away from heat and direct sunlight.
  - Ensure good ventilation/exhaustion at the workplace.
  - Prevent formation of aerosols.
- Information about fire - and explosion protection:
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
  - Storage:
    - Requirements to be met by storerooms and receptacles: No special requirements.
    - Information about storage in one common storage facility: Not required.
    - Further information about storage conditions: Keep container tightly sealed.
    - Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- **8.1 Control parameters**
  - Ingredients with limit values that require monitoring at the workplace:
    - The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNEL (Derived No Effect Level) for workers		
<b>94-36-0 dibenzoyl peroxide</b>		
Dermal	Long-term - systemic effects, worker	6.6 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	11.75 mg/m <sup>3</sup> (Worker)
· DNEL (Derived No Effect Level) for the general population		
<b>94-36-0 dibenzoyl peroxide</b>		
Oral	Long-term - systemic effects, general population	1.65 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	3.3 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	2.9 mg/m <sup>3</sup> (General population)
· PNEC (Predicted No Effect Concentration) values		
<b>94-36-0 dibenzoyl peroxide</b>		
Aquatic compartment - freshwater		0.000602 mg/l (Freshwater)
Aquatic compartment - sediment in freshwater		0.338 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.0338 mg/kg sed dw (Sediment marine water)
Sewage treatment plant		0.35 mg/l (stp)
Oral secondary poisoning		6.67 mg/kg food (Food sec poisoning)

- Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

**Trade name: PEROXAN BP-PASTE 50 PF**

(Contd. of page 3)

**· 8.2 Exposure controls**

- Personal protective equipment:  
 · General protective and hygienic measures:
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.
  - Avoid contact with the eyes.
  - Avoid contact with the eyes and skin.
- Respiratory protection:
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands:
  - Protective gloves
  - The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
  - Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
  - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves
  - Butyl rubber, BR
  - Fluorocarbon rubber (Viton)
  - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
  - Recommended thickness of the material:  $\geq 0.3$  mm
- Penetration time of glove material
  - The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
  - For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
- For the permanent contact gloves made of the following materials are suitable:
  - Butyl rubber, BR
  - Fluorocarbon rubber (Viton)
- As protection from splashes gloves made of the following materials are suitable:
  - Nitrile rubber, NBR
- Not suitable are gloves made of the following materials:
  - Leather gloves
  - Strong material gloves
- Eye protection:
  - Tightly sealed goggles

**SECTION 9: Physical and chemical properties**

**· 9.1 Information on basic physical and chemical properties**

- General Information
- Appearance:
  - Form: Pasty
  - Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- pH-value at 20 °C: 6
- Change in condition
  - Melting point/freezing point: Undetermined.
  - Initial boiling point and boiling range: Undetermined.
- Flash point: Not applicable.
- Flammability (solid, gas): Not applicable.
- Ignition temperature: 370 °C
- Decomposition temperature: Not determined.
- Auto-ignition temperature: Product is not selfigniting.
- Explosive properties: Product does not present an explosion hazard.  
 May cause fire.

(Contd. on page 5)

**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 57

Revision: 05.08.2020

**Trade name: PEROXAN BP-PASTE 50 PF**

(Contd. of page 4)

· Explosion limits: Lower: Upper:	Not determined. Not determined.
· Vapour pressure at 20 °C:	1 hPa
· Density at 20 °C: · Relative density · Vapour density · Evaporation rate	1.15 g/cm <sup>3</sup> (DIN 51757, ASTM D 1298) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C: Kinematic:	20,000 mPas (Brookfield, ASTM D1544) Not determined.
· Solvent content: VOC (2004/42/EC):	0.00 %
· Solids content:	85.0 %
· <b>9.2 Other information</b>	No further relevant information available.
· Additional information Decomposition temperature Active oxygen content	SADT 50 °C 3.3 %

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
<b>ATE (Acute Toxicity Estimates)</b>			
Oral	LD50	20,000 mg/kg	

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information**

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.

(Contd. on page 6)

**Trade name: PEROXAN BP-PASTE 50 PF**

(Contd. of page 5)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Ecotoxicological effects:
- Remark: Very toxic for fish
- Additional ecological information:
- General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
 Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
 Also poisonous for fish and plankton in water bodies.  
 Very toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP13	Sensitising
HP14	Ecotoxic

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

**SECTION 14: Transport information**

· <b>14.1 UN-Number</b>	UN3108
· ADR/RID/ADN, IMDG, IATA	
· <b>14.2 UN proper shipping name</b>	3108 ORGANIC PEROXIDE TYPE E, SOLID, ENVIRONMENTALLY HAZARDOUS
· ADR/RID/ADN	ORGANIC PEROXIDE TYPE E, SOLID (isononylbenzoaat), MARINE POLLUTANT
· IMDG	ORGANIC PEROXIDE TYPE E, SOLID
· IATA	
· <b>14.3 Transport hazard class(es)</b>	
· ADR/RID/ADN	
· Class	5.2 (P1) Organic peroxides.
· Label	5.2
· IMDG, IATA	
· Class	5.2 Organic peroxides.
· Label	5.2
· <b>14.4 Packing group</b>	Void
· ADR/RID/ADN, IMDG, IATA	
· <b>14.5 Environmental hazards:</b>	
· Marine pollutant:	No Symbol (fish and tree)
· Special marking (ADR/RID/ADN):	Symbol (fish and tree)
· <b>14.6 Special precautions for user</b>	Warning: Organic peroxides.
· EMS Number:	F-J,S-R
· Stowage Category	D
· Stowage Code	SW1 Protected from sources of heat.

(Contd. on page 7)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 57

Revision: 05.08.2020

**Trade name: PEROXAN BP-PASTE 50 PF**

(Contd. of page 6)

· Segregation Code	SG35 Stow "separated from" SGG1-acids SG36 Stow "separated from" SGG18-alkalis.
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN	
· Limited quantities (LQ)	500 g
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	500 g
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 3108 ORGANIC PEROXIDE TYPE E, SOLID, 5.2, ENVIRONMENTALLY HAZARDOUS

### SECTION 15: Regulatory information

#### · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I  
None of the ingredients is listed.
- Seveso category  
P6b SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES  
E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements  
50 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements  
200 t
- REGULATION (EC) No 1907/2006 ANNEX XVII  
Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

#### · 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases  
H241 Heating may cause a fire or explosion.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.
- Classification according to Regulation (EC) No 1272/2008  
The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 8)



**Safety data sheet  
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 57

Revision: 05.08.2020

**Trade name: PEROXAN BP-PASTE 50 PF**

(Contd. of page 7)

Organic peroxides	On basis of test data
Serious eye damage/eye irritation Skin sensitisation Hazardous to the aquatic environment - short-term (acute) aquatic hazard Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- Department issuing SDS:
- Contact:
- Abbreviations and acronyms:

**Research and Development**Herman van den Berg, tel: +31 182 372177, e-mail: [safety@de-ijssel-coatings.nl](mailto:safety@de-ijssel-coatings.nl)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Org. Perox. B: Organic peroxides – Type B

Org. Perox. E: Organic peroxides – Type E/F

Acute Tox. 4: Acute toxicity - oral – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Literature data and/or investigation reports are available through the manufacturer.

- Sources:
- \* Data compared to the previous version altered.