

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

- Trade name: **Poltix Resin M-EB**
- Article number: 282-20000
- UFI: Y143-HOCT-D00V-56D8
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- Sector of Use
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU19 Building and construction work
- Process category PROC19 Manual activities involving hand contact
- Environmental release category
 - ERC5 Use at industrial site leading to inclusion into/onto article
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
 - AC13 Plastic articles
- Article category
- Application of the substance / the mixture
 - See our technical datasheet for application details of this product.
 - Polyester resin

1.3 Details of the supplier of the safety data sheet

- Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl
- Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
 Office hours: working days from 08:00 to 17:00 hrs.


SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

- Classification according to Regulation (EC) No 1272/2008

 GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

 GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

 GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· Hazard pictograms   
 GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling: styrene
cobalt(II) 2-ethylhexanoate
methacrylic acid, monoester with propane-1,2-diol

· Hazard statements
 H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H361d Suspected of damaging the unborn child.

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 11

Revision: 23.03.2021

Trade name: Poltix Resin M-EB

(Contd. of page 1)

<ul style="list-style-type: none"> · Precautionary statements · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: · vPvB: 	<p>H335 May cause respiratory irritation.</p> <p>H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P260 Do not breathe dust/fume/gas/mist/vapours/spray.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p> <p>Not applicable.</p> <p>Not applicable.</p>
---	--

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32	styrene ⚠ Flam. Liq. 3, H226; ⚠ Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	25 – 50%
CAS: 27813-02-1 EINECS: 248-666-3 Index number: 607-125-00-5 Reg.nr.: 01-2119490226-37	methacrylic acid, monoester with propane-1,2-diol ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	0.5 – 1%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-21195-24678-29	cobalt(II) 2-ethylhexanoate ⚠ Repr. 2, H361f; ⚠ Aquatic Acute 1, H400; ⚠ Eye Irrit. 2, H319; Skin Sens. 1A, H317; Aquatic Chronic 3, H412	0.1 – 0.5%
CAS: 123-31-9 EINECS: 204-617-8 Index number: 604-005-00-4 Reg.nr.: 01-2119524016-51	1,4-dihydroxybenzene ⚠ Muta. 2, H341; Carc. 2, H351; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	≤ 0.1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

<ul style="list-style-type: none"> · General information: · After inhalation: · After skin contact: · After eye contact: · After swallowing: · 4.2 Most important symptoms and effects, both acute and delayed · 4.3 Indication of any immediate medical attention and special treatment needed 	<p>Immediately remove any clothing soiled by the product.</p> <p>Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.</p> <p>Supply fresh air and to be sure call for a doctor.</p> <p>In case of unconsciousness place patient stably in side position for transportation.</p> <p>Immediately wash with water and soap and rinse thoroughly.</p> <p>Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.</p> <p>If symptoms persist consult doctor.</p> <p>No further relevant information available.</p> <p>No further relevant information available.</p>
--	---

SECTION 5: Firefighting measures**5.1 Extinguishing media**

· Suitable extinguishing agents: CO2 or powder. Fight larger fires with alcohol resistant foam.

(Contd. on page 3)

Trade name: Poltix Resin M-EB

(Contd. of page 2)

- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage: Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNEL (Derived No Effect Level) for workers

100-42-5 styrene

Dermal	Long-term - systemic effects, worker	406 mg/kg bw/day (Worker)
Inhalative	Acute - systemic effects, worker	289 mg/m ³ (Worker)
	Acute - local effects, worker	306 mg/m ³ (Worker)
	Long-term - systemic effects, worker	85 mg/m ³ (Worker)

(Contd. on page 4)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 11

Revision: 23.03.2021

Trade name: Poltix Resin M-EB

(Contd. of page 3)

27813-02-1 methacrylic acid, monoester with propane-1,2-diol		
Dermal	Long-term - systemic effects, worker	4.2 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	14.7 mg/m ³ (Worker)
136-52-7 cobalt(II) 2-ethylhexanoate		
Inhalative	Long-term - local effects, worker	0.235 mg/m ³ (Worker)
123-31-9 1,4-dihydroxybenzene		
Dermal	Long-term - systemic effects, worker	128 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	7 mg/m ³ (Worker)
	Long-term - local effects, worker	1 mg/m ³ (Worker)
· DNEL (Derived No Effect Level) for the general population		
100-42-5 styrene		
Oral	Long-term - systemic effects, general population	2.1 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	343 mg/kg bw/day (General population)
Inhalative	Acute - systemic effects, general population	174.25 mg/m ³ (General population)
	Acute - local effects, general population	182.75 mg/m ³ (General population)
	Long-term - systemic effects, general population	10.2 mg/m ³ (General population)
27813-02-1 methacrylic acid, monoester with propane-1,2-diol		
Oral	Long-term - systemic effects, general population	2.5 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	2.5 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	8.8 mg/m ³ (General population)
136-52-7 cobalt(II) 2-ethylhexanoate		
Oral	Long-term - systemic effects, general population	0.0558 mg/kg bw/day (General population)
Inhalative	Long-term - local effects, general population	0.037 mg/m ³ (General population)
123-31-9 1,4-dihydroxybenzene		
Dermal	Long-term - systemic effects, general population	64 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	1.74 mg/m ³ (General population)
	Long-term - local effects, general population	0.5 mg/m ³ (General population)
· PNEC (Predicted No Effect Concentration) values		
100-42-5 styrene		
Aquatic compartment - freshwater		0.028 mg/l (Sediment freshwater)
Aquatic compartment - marine water		0.0028 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		0.04 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater		0.0614 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.0614 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		0.2 mg/kg dw (Soil)
Sewage treatment plant		5 mg/l (stp)
27813-02-1 methacrylic acid, monoester with propane-1,2-diol		
Aquatic compartment - freshwater		0.904 mg/l (Freshwater)
Aquatic compartment - marine water		0.904 mg/l (Marine water)
Aquatic compartment - sediment in freshwater		6.28 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		6.28 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		7.9 mg/kg dw (Soil)
Sewage treatment plant		10 mg/l (stp)
136-52-7 cobalt(II) 2-ethylhexanoate		
Aquatic compartment - freshwater		0.00149 mg/l (Freshwater)
Aquatic compartment - marine water		0.0069 mg/l (Marine water) ((Co))
Aquatic compartment - sediment in freshwater		27.8 mg/kg sed dw (Sediment freshwater) ((Co))
Aquatic compartment - sediment in marine water		17.8 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		23.1 mg/kg dw (Soil) ((CoH))
Sewage treatment plant		1.08 mg/l (stp) ((Co))
123-31-9 1,4-dihydroxybenzene		
Aquatic compartment - freshwater		0.000114 mg/l (Freshwater)
Aquatic compartment - marine water		0.0000114 mg/l (Marine water)

(Contd. on page 5)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 11

Revision: 23.03.2021

Trade name: Poltix Resin M-EB

(Contd. of page 4)

Aquatic compartment - water, intermittent releases	0.00134 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	0.00098 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.000097 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	0.000129 mg/kg dw (Soil)
Sewage treatment plant	0.71 mg/l (stp)
· Additional information:	The lists valid during the making were used as basis.
· 8.2 Exposure controls	
· Personal protective equipment:	
· General protective and hygienic measures:	Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.
· Respiratory protection:	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
· Protection of hands:	Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
· Material of gloves	The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Recommended thickness of the material: ≥ 0.3 mm
· Penetration time of glove material	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
· For the permanent contact gloves made of the following materials are suitable:	Butyl rubber, BR Fluorocarbon rubber (Viton)
· As protection from splashes gloves made of the following materials are suitable:	Nitrile rubber, NBR
· Not suitable are gloves made of the following materials:	Leather gloves Strong material gloves
· Eye protection:	Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Fluid
Colour:	Pink
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	145 °C
· Flash point:	33 °C (DIN 51758)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	480 °C

(Contd. on page 6)

Trade name: Poltix Resin M-EB

(Contd. of page 5)

· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	1.2 Vol % 8.9 Vol %
· Vapour pressure at 20 °C:	6 hPa
· Density at 20 °C: · Relative density · Vapour density · Evaporation rate	1.1 g/cm ³ (DIN 51757, ASTM D 1298) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C: Kinematic at 40 °C:	550 mPas (Brookfield, ASTM D1544) 30 mm ² /s
· Solvent content: Organic solvents: VOC (2004/42/EC):	37.5 % 37.50 %
· Solids content:	50.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*** SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
100-42-5 styrene			
Oral	LD50	5000 mg/kg	(Rat)
123-31-9 1,4-dihydroxybenzene			
Oral	LD50	320 mg/kg	(Rat)

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging the unborn child.
- STOT-single exposure May cause respiratory irritation.

(Contd. on page 7)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 11

Revision: 23.03.2021

Trade name: Poltix Resin M-EB

(Contd. of page 6)

- STOT-repeated exposure Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.

Type of test	Effective concentration	Method	Assessment
100-42-5 styrene			
Oral	EC50	5.1 mg/l (Daphnia magna)	
Inhalative	LC50/4 h	24 mg/l (Rat)	
	LC50/96 h	25 mg/l (Lepomis macrochirus)	

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Ecotoxicological effects:
- Remark: Harmful to fish
- Additional ecological information:
- General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP10	Toxic for reproduction
HP14	Ecotoxic

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number	
· ADR/RID/ADN, IMDG, IATA	UN1866
· 14.2 UN proper shipping name	
· ADR/RID/ADN	1866 RESIN SOLUTION
· IMDG, IATA	RESIN SOLUTION
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class	3 (F1) Flammable liquids.
· Label	3

· IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3

(Contd. on page 8)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 11

Revision: 23.03.2021

Trade name: Poltix Resin M-EB

(Contd. of page 7)

· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E,S-E A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code · Remarks:	3 D/E In packsize up to 450 liter exempt from ADR according to ADR 2.2.3.1.5.
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Remarks:	In packaging up to 30 litres exempt according to IMDG 2.3.2.5.
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

*** SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I
None of the ingredients is listed.
- Seveso category
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII
Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	37.5

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

— EU —

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 11

Revision: 23.03.2021

Trade name: Poltix Resin M-EB

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H226 Flammable liquid and vapour.
 - H302 Harmful if swallowed.
 - H304 May be fatal if swallowed and enters airways.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H341 Suspected of causing genetic defects.
 - H351 Suspected of causing cancer.
 - H361d Suspected of damaging the unborn child.
 - H361f Suspected of damaging fertility.
 - H372 Causes damage to organs through prolonged or repeated exposure.
 - H400 Very toxic to aquatic life.
 - H412 Harmful to aquatic life with long lasting effects.

- Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	On basis of test data
Skin corrosion/irritation Serious eye damage/eye irritation Skin sensitisation Reproductive toxicity Specific target organ toxicity (single exposure) Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- Department issuing SDS: Research and Development
- Contact: Saïda El Asjadi, tel: +31 182 372177, e-mail: safety@de-ijsel-coatings.nl
- Abbreviations and acronyms:
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Acute Tox. 4: Acute toxicity – Category 4
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Skin Sens. 1: Skin sensitisation – Category 1
 - Skin Sens. 1A: Skin sensitisation – Category 1A
 - Muta. 2: Germ cell mutagenicity – Category 2
 - Carc. 2: Carcinogenicity – Category 2
 - Repr. 2: Reproductive toxicity – Category 2
 - Repr. 2: Reproductive toxicity – Category 2
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 - STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
 - Asp. Tox. 1: Aspiration hazard – Category 1
 - Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
 - Literature data and/or investigation reports are available through the manufacturer.
- Sources:
- * Data compared to the previous version altered.