

05.08.2020

Kit components

Product code	Description
--------------	-------------

341	Variopox XD-D set
------------	--------------------------

Components:

339	Variopox Topcoat XD-D basis
-----	-----------------------------

340	Variopox Topcoat XD-D verharder
-----	---------------------------------

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 4

Revision: 04.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Variopox Topcoat XD-D basis**

Article number: 339

UFI: X5R3-D09A-Q007-PAAN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU19 Building and construction work

Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC19 Manual activities involving hand contact

Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

Article category AC13 Plastic articles

Application of the substance / the mixture See our technical datasheet for application details of this product.
Epoxy resin

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
Office hours: working days from 08:00 to 17:00 hrs.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

 GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

 GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

bis[4-(2,3-epoxypropoxy)phenyl]propane oxirane, mono[(C12-14-alkyloxy)methyl] derivs
Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate

Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P261 Avoid breathing mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection / face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2020

Version number 4

Revision: 04.08.2020

Trade name: Variopox Topcoat XD-D basis

(Contd. of page 1)

P333+P313
P501If skin irritation or rash occurs: Get medical advice/attention.
Dispose of contents/container in accordance with local/regional/
national/international regulations.**2.3 Other hazards**

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26	bis[4-(2,3-epoxypropoxy)phenyl]propane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	50 – 100%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4	oxirane, mono[(C12-14-alkyloxy)methyl] derivs ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	10 – 25%
CAS: 41556-26-7 EINECS: 255-437-1	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1, H317	0.1 – 0.5%
CAS: 82919-37-7 EINECS: 280-060-4	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ⚠ Skin Sens. 1, H317	0.1 – 0.5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

- Protective equipment: No special measures required.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Not required.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Trade name: Variopox Topcoat XD-D basis

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
- Information about fire - and explosion protection: No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: Keep container tightly sealed.
 - Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- **8.1 Control parameters**
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNEL (Derived No Effect Level) for workers		
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Dermal	Long-term - systemic effects, worker	0.75 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	4.93 mg/m ³ (Worker)
· DNEL (Derived No Effect Level) for the general population		
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Oral	Long-term - systemic effects, general population	0.5 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	0.0893 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	0.87 mg/m ³ (General population)
· PNEC (Predicted No Effect Concentration) values		
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Aquatic compartment - freshwater		0.006 mg/l (Freshwater)
Aquatic compartment - marine water		0.001 mg/l (Marine water)
Aquatic compartment - sediment in freshwater		0.341 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.034 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		0.065 mg/kg dw (Soil)
Sewage treatment plant		10 mg/l (stp)
Oral secondary poisoning		11 mg/kg food (Food sec poisoning)

- Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

Trade name: Variopox Topcoat XD-D basis

(Contd. of page 3)

· 8.2 Exposure controls

- Personal protective equipment:
 - General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands: Protective gloves
 The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
- Not suitable are gloves made of the following materials: Leather gloves
Strong material gloves
- Eye protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information	
· Appearance:	
Form:	Fluid
Colour:	Colourless
· Odour:	Nearly odourless
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
· Flash point:	Not applicable.
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.14 g/cm ³ (DIN 51757, ASTM D 1298)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Fully miscible.

(Contd. on page 5)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 4

Revision: 04.08.2020

Trade name: Variopox Topcoat XD-D basis

(Contd. of page 4)

· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic at 20 °C: Kinematic:	500 – 700 mPas (Brookfield, ASTM D1544) Not determined.
· Solvent content: VOC (2004/42/EC):	0.00 %
Solids content:	0.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Ecotoxicological effects:
- Remark: Toxic for fish
- Additional ecological information:
- General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

(Contd. on page 6)

Trade name: Variopox Topcoat XD-D basis

(Contd. of page 5)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
HP4	Irritant - skin irritation and eye damage
HP13	Sensitising
HP14	Ecotoxic

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN3082
· 14.2 UN proper shipping name · ADR/RID/ADN · IMDG · IATA	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-epoxypropoxy)phenyl]propane)
· 14.3 Transport hazard class(es) · ADR/RID/ADN · Class · Label	9 (M6) Miscellaneous dangerous substances and articles. 9
· IMDG, IATA · Class · Label	9 Miscellaneous dangerous substances and articles. 9
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR/RID/ADN): · Special marking (IATA):	Product contains environmentally hazardous substances: bis[4-(2,3-epoxypropoxy)phenyl]propane Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information: · ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 -
· IMDG · Limited quantities (LQ)	5L

(Contd. on page 7)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 3

Revision: 04.08.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Variopox Topcoat XD-D verharder**

Article number: 340

UFI: A3R3-V0KX-D00Q-0YRK

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU19 Building and construction work

Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC19 Manual activities involving hand contact

Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

Article category AC13 Plastic articles

Application of the substance / the mixture See our technical datasheet for application details of this product.
Epoxy curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
Office hours: working days from 08:00 to 17:00 hrs.


SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

 GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

 GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

 GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

  
GHS05 GHS07 GHS09

Signal word Danger

Hazard-determining components of labelling:

Hazard statements Propylidynetrimethanol, propoxylated, reaction products with ammonia

H302+H312 Harmful if swallowed or in contact with skin.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P330 Rinse mouth.

(Contd. on page 2)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 3

Revision: 04.08.2020

Trade name: Variopox Topcoat XD-D verharder

(Contd. of page 1)

P362+P364
P501Take off contaminated clothing and wash it before reuse.
Dispose of contents/container in accordance with local/regional/
national/international regulations.**· 2.3 Other hazards**

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**· 3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 39423-51-3 NLP: 500-105-6	Propylidynetrimethanol, propoxylated, reaction products with ammonia Eye Dam. 1, H318; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312	50 – 100%
-----------------------------------	---	-----------

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media**

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

· 5.3 Advice for firefighters

- Protective equipment: No special measures required.

SECTION 6: Accidental release measures**· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

· 6.4 Reference to other sections

Dispose contaminated material as waste according to item 13. See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 3)

Trade name: Variopox Topcoat XD-D verharder

(Contd. of page 2)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- Information about fire - and explosion protection: No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage: Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- **8.1 Control parameters**
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNEL (Derived No Effect Level) for workers	
39423-51-3 Propylidynetrimehanol, propoxylated, reaction products with ammonia	
Inhalative	Long-term - systemic effects, worker 14 mg/m ³ (Worker)
· DNEL (Derived No Effect Level) for the general population	
39423-51-3 Propylidynetrimehanol, propoxylated, reaction products with ammonia	
Inhalative	Long-term - systemic effects, general population 3.48 mg/m ³ (General population)
· PNEC (Predicted No Effect Concentration) values	
39423-51-3 Propylidynetrimehanol, propoxylated, reaction products with ammonia	
Aquatic compartment - freshwater	0.044 mg/l (Freshwater)
Aquatic compartment - marine water	0.00044 mg/l (Marine water)
Aquatic compartment - water, intermittent releases	0.044 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	0.02 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.002 mg/kg sed dw (Sediment marine water)

- Additional information: The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- Personal protective equipment:
- General protective and hygienic measures:
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.
- Respiratory protection: Not required.
- Protection of hands: Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Trade name: Variopox Topcoat XD-D verharder

(Contd. of page 4)

- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity: Harmful if swallowed or in contact with skin.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
ATE (Acute Toxicity Estimates)			
Oral	LD50	< 526 mg/kg	
Dermal	LD50	< 1,158 mg/kg	

- Primary irritant effect:
- Skin corrosion/irritation: Based on available data, the classification criteria are not met.
- Serious eye damage/irritation: Causes serious eye damage.
- Respiratory or skin sensitisation: Based on available data, the classification criteria are not met.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- Aspiration hazard: Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability**: No further relevant information available.
- **12.3 Bioaccumulative potential**: No further relevant information available.
- **12.4 Mobility in soil**: No further relevant information available.
- Ecotoxicological effects:
- Remark: Toxic for fish
- Additional ecological information:
- General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Must not reach sewage water or drainage ditch undiluted or unneutralised.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Other adverse effects**: No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
HP4	Irritant - skin irritation and eye damage
HP6	Acute Toxicity
HP14	Ecotoxic

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.08.2020

Version number 3

Revision: 04.08.2020

Trade name: Variopox Topcoat XD-D verharder

(Contd. of page 5)

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA 	UN3082
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR/RID/ADN · IMDG · IATA 	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propylidyntrimethanol, propoxylated, reaction products with ammonia) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propylidyntrimethanol, propoxylated, reaction products with ammonia), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Propylidyntrimethanol, propoxylated, reaction products with ammonia)
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR/RID/ADN · Class · Label 	9 (M6) Miscellaneous dangerous substances and articles. 9
<ul style="list-style-type: none"> · IMDG, IATA · Class · Label 	9 Miscellaneous dangerous substances and articles. 9
<ul style="list-style-type: none"> · 14.4 Packing group · ADR/RID/ADN, IMDG, IATA 	III
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR/RID/ADN): · Special marking (IATA): 	Product contains environmentally hazardous substances: Propylidyntrimethanol, propoxylated, reaction products with ammonia Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	Warning: Miscellaneous dangerous substances and articles. 90 F-A,S-F A
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 -
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PROPYLIDYNETRIMETHANOL, PROPOXYLATED, REACTION PRODUCTS WITH AMMONIA), 9, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
 - Named dangerous substances - ANNEX I
- None of the ingredients is listed.

(Contd. on page 7)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 05.08.2020

Version number 3

Revision: 04.08.2020

Trade name: Variopox Topcoat XD-D verharder

(Contd. of page 6)

- Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H318 Causes serious eye damage.
H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

Acute toxicity - oral Acute toxicity - dermal Serious eye damage/eye irritation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

- Department issuing SDS: Research and Development
- Contact: Herman van den Berg, tel: +31 182 372177, e-mail: safety@de-ijsel-coatings.nl
- Abbreviations and acronyms:
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Acute Tox. 4: Acute toxicity - oral – Category 4
 - Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Sources: Literature data and/or investigation reports are available through the manufacturer.