

23.03.2021

Kit components

Product code	Description
--------------	-------------

368	Variopox LG plamuur set
------------	--------------------------------

Components:

367	Epoxy LG filler hardener
-----	--------------------------

366	Epoxy LG Filler base component
-----	--------------------------------

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Epoxy LG filler hardener**

Article number: 367
 UFI: 77Q4-H0V8-W00E-6T97

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 SU19 Building and construction work
 Product category PC9b Fillers, putties, plasters, modelling clay
 Process category PROC19 Manual activities involving hand contact
 Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article
 ERC8c Widespread use leading to inclusion into/onto article (indoor)
 ERC8f Widespread use leading to inclusion into/onto article (outdoor)
 Article category AC13 Plastic articles
 Application of the substance / the mixture See our technical datasheet for application details of this product.
 Epoxy filler
 Epoxy curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
 Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
 Office hours: working days from 08:00 to 17:00 hrs.


SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008


 GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

 GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

 GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

 GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

Hazard pictograms

The product is classified and labelled according to the CLP regulation.

   
 GHS05 GHS07 GHS08 GHS09

Signal word Danger

Hazard-determining components of labelling:

3-aminomethyl-3,5,5-trimethylcyclohexylamine
 Salicylic acid
 m-phenylenebis(methylamine)
 Benzyl alcohol
 phenol, styrenated
 Phenol, methylstyrenated

Hazard statements

H302 Harmful if swallowed.
 H314 Causes severe skin burns and eye damage.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.03.2021

Version number 58

Revision: 23.03.2021

Trade name: Epoxy LG filler hardener

(Contd. of page 1)

<ul style="list-style-type: none"> · Precautionary statements 	<p>H317 May cause an allergic skin reaction. H361d Suspected of damaging the unborn child. H411 Toxic to aquatic life with long lasting effects.</p> <p>P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER/doctor. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p>
<ul style="list-style-type: none"> · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: · vPvB: 	<p>Not applicable. Not applicable.</p>

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine ☠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ☠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10 – 25%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38	Benzyl alcohol ☠ Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	2.5 – 10%
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	m-phenylenebis(methylamine) ☠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ☠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	2.5 – 10%
CAS: 68609-08-5 EC number: 614-657-1	Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer ☠ Skin Corr. 1B, H314; Eye Dam. 1, H318	2.5 – 10%
CAS: 69-72-7 EINECS: 200-712-3 Reg.nr.: 01-2119486984-17	Salicylic acid ☠ Repr. 2, H361d; ☠ Eye Dam. 1, H318; ☠ Acute Tox. 4, H302	2.5 – 10%
CAS: 61788-44-1 EINECS: 262-975-0 Reg.nr.: 01-2119980970-27	phenol, styrenated ☠ Aquatic Chronic 2, H411; ☠ Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5 – 10%
CAS: 68512-30-1 EINECS: 270-966-8 Reg.nr.: 01-211955274-38	Phenol, methylstyrenated ☠ Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	2.5 – 10%
CAS: 112-53-8 EINECS: 203-982-0 Reg.nr.: 01-2119485976-15	Lauryl alcohol ☠ Aquatic Acute 1, H400; Aquatic Chronic 2, H411; ☠ Eye Irrit. 2, H319	0.5 – 1%
CAS: 61788-46-3 EINECS: 262-977-1 Index number: 612-285-00-4 Reg.nr.: 01-2119473798-17	Amines, coco alkyl ☠ STOT RE 2, H373; Asp. Tox. 1, H304; ☠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ☠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); ☠ Acute Tox. 4, H302; STOT SE 3, H335	0.5 – 1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Trade name: Epoxy LG filler hardener

(Contd. of page 2)

- After inhalation: Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Call for a doctor immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- Information about fire - and explosion protection: Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage: No special requirements.
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

(Contd. on page 4)

Trade name: Epoxy LG filler hardener

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection
8.1 Control parameters

- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNEL (Derived No Effect Level) for workers		
2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Inhalative	Acute - systemic effects, worker	0.073 mg/m ³ (Worker)
	Acute - local effects, worker	20.1 mg/m ³ (Worker)
100-51-6 Benzyl alcohol		
Dermal	Long-term - systemic effects, worker	8 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	22 mg/m ³ (Worker)
1477-55-0 m-phenylenebis(methylamine)		
Dermal	Long-term - systemic effects, worker	0.33 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	1.2 mg/m ³ (Worker)
68609-08-5 Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer		
Dermal	Long-term - systemic effects, worker	560 mg/kg bw/day (Worker)
Inhalative	Acute - local effects, worker	9.87 mg/m ³ (Worker)
	Long-term - systemic effects, worker	247 mg/m ³ (Worker)
69-72-7 Salicylic acid		
Dermal	Long-term - systemic effects, worker	2.3 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	5 mg/m ³ (Worker)
61788-44-1 phenol, styrenated		
Dermal	Long-term - systemic effects, worker	3.5 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	7.4 mg/m ³ (Worker)
68512-30-1 Phenol, methylstyrenated		
Dermal	Long-term - systemic effects, worker	3.5 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	1.4 mg/m ³ (Worker)
112-53-8 Lauryl alcohol		
Dermal	Long-term - systemic effects, worker	125 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	220 mg/m ³ (Worker)
61788-46-3 Amines, coco alkyl		
Dermal	Long-term - systemic effects, worker	0.09 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	0.38 mg/m ³ (Worker)
· DNEL (Derived No Effect Level) for the general population		
2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine		
Oral	Long-term - systemic effects, general population	0.526 mg/kg bw/day (General population)
100-51-6 Benzyl alcohol		
Oral	Long-term - systemic effects, general population	4 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	4 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	5.4 mg/m ³ (General population)
68609-08-5 Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer		
Oral	Acute - systemic effects, general population	0.99 mg/kg bw/day (General population)
	Long-term - systemic effects, general population	0.33 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	0.67 mg/kg bw/day (General population)
	Acute - systemic effects, general population	1.74 mg/m ³ (General population)
Inhalative	Long-term - systemic effects, general population	87 mg/m ³ (General population)

(Contd. on page 5)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 58

Revision: 23.03.2021

Trade name: Epoxy LG filler hardener

(Contd. of page 4)

69-72-7 Salicylic acid	
Oral	Long-term - systemic effects, general population 1 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population 1 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population 4 mg/m ³ (General population)
· PNEC (Predicted No Effect Concentration) values	
2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine	
Aquatic compartment - freshwater	0.06 mg/l (Freshwater)
Aquatic compartment - marine water	0.006 mg/l (Marine water)
Aquatic compartment - water, intermittent releases	0.23 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	5.784 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.578 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	1.121 mg/kg dw (Soil)
Sewage treatment plant	3.18 mg/l (stp)
100-51-6 Benzyl alcohol	
Aquatic compartment - freshwater	1 mg/l (Freshwater)
Aquatic compartment - marine water	0.1 mg/l (Marine water)
1477-55-0 m-phenylenebis(methylamine)	
Aquatic compartment - freshwater	0.094 mg/l (Freshwater)
Aquatic compartment - marine water	0.0094 mg/l (Marine water)
Aquatic compartment - water, intermittent releases	0.152 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	0.43 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.043 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	0.045 mg/kg dw (Soil)
Sewage treatment plant	10 mg/l (stp)
68609-08-5 Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-,reaction products with bisphenol A diglycidyl ether homopolymer	
Aquatic compartment - freshwater	0.002 mg/l (Freshwater)
Aquatic compartment - marine water	0 mg/l (Marine water)
Aquatic compartment - sediment in freshwater	10.5 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	1.05 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	2.1 mg/kg dw (Soil)
Sewage treatment plant	3.1 mg/l (stp)
69-72-7 Salicylic acid	
Aquatic compartment - freshwater	0.2 mg/l (Freshwater)
Aquatic compartment - marine water	0.02 mg/l (Marine water)
61788-44-1 phenol, styrenated	
Aquatic compartment - freshwater	0.03 mg/l (Freshwater)
Aquatic compartment - marine water	0.003 mg/l (Marine water)
68512-30-1 Phenol, methylstyrenated	
Aquatic compartment - freshwater	0.014 mg/l (Freshwater)
Aquatic compartment - marine water	0.0014 mg/l (Marine water)
112-53-8 Lauryl alcohol	
Aquatic compartment - freshwater	0.0028 mg/l (Freshwater)
Aquatic compartment - marine water	0.00028 mg/l (Marine water)
61788-46-3 Amines, coco alkyl	
Aquatic compartment - freshwater	0.00026 mg/l (Freshwater)
Aquatic compartment - marine water	0.000026 mg/l (Marine water)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

(Contd. on page 6)

Trade name: Epoxy LG filler hardener

(Contd. of page 5)

<ul style="list-style-type: none"> · Respiratory protection: · Protection of hands: · Material of gloves · Penetration time of glove material · For the permanent contact gloves made of the following materials are suitable: · As protection from splashes gloves made of the following materials are suitable: · Not suitable are gloves made of the following materials: · Eye protection: 	<p>Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.</p> <p>In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</p> <p>Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation</p> <p>Nitrile rubber, NBR The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Recommended thickness of the material: ≥ 0.3 mm</p> <p>The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).</p> <p>Nitrile rubber, NBR</p> <p>Nitrile rubber, NBR</p> <p>Leather gloves Strong material gloves Tightly sealed goggles</p>
--	---

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Fluid
Colour:	According to product specification
· Odour: Characteristic	
· Odour threshold: Not determined.	
· pH-value at 20 °C: 11	
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	205 °C
· Flash point: 101 °C (Pensky Martens, ASTM D93)	
· Flammability (solid, gas): Not applicable.	
· Ignition temperature: 435 °C	
· Decomposition temperature: Not determined.	
· Auto-ignition temperature: Product is not selfigniting.	
· Explosive properties: Product does not present an explosion hazard.	
· Explosion limits:	
Lower:	0.0 Vol %
Upper:	0.0 Vol %
· Vapour pressure at 20 °C: 0.1 hPa	
· Density at 20 °C: 0.877 g/cm ³ (DIN 51757, ASTM D 1298)	
· Relative density: Not determined.	
· Vapour density: Not determined.	

(Contd. on page 7)

Trade name: Epoxy LG filler hardener

(Contd. of page 6)

· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents: VOC (2004/42/EC):	8.6 % 8.56 %
Solids content:	90.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Harmful if swallowed.
- LD/LC50 values relevant for classification:

· Components	Type	Value	Species
ATE (Acute Toxicity Estimates)			
Oral	LD50	1612 mg/kg	
Dermal	LD50	5138 mg/kg	
100-51-6 Benzyl alcohol			
Oral	LD50	1230 mg/kg (Rat)	
Dermal	LD50	2000 mg/kg (Rabbit)	
1477-55-0 m-phenylenebis(methylamine)			
Oral	LD50	1040 mg/kg (Rat)	
69-72-7 Salicylic acid			
Oral	LD50	891 mg/kg (Rat)	
112-53-8 Lauryl alcohol			
Oral	LD50	12800 mg/kg (Rat)	

- Primary irritant effect:
- Skin corrosion/irritation Causes severe skin burns and eye damage.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Suspected of damaging the unborn child.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 8)

Trade name: Epoxy LG filler hardener

(Contd. of page 7)

SECTION 12: Ecological information
12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

· Type of test Effective concentration Method Assessment

ATE (Acute Toxicity Estimates)

Inhalative | LC50/4 h | 23 mg/l

1477-55-0 m-phenylenebis(methylamine)

Inhalative | LC50/4 h | 2.4 mg/l (Rat)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

· Ecotoxicological effects:

· Remark:

Toxic for fish

· Additional ecological information:

· General notes:

 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Must not reach sewage water or drainage ditch undiluted or unneutralised.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms

12.5 Results of PBT and vPvB assessment

· PBT:

Not applicable.

· vPvB:

Not applicable.

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations
13.1 Waste treatment methods

· Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00 | WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00 | wastes from MFSU and removal of paint and varnish

08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances

HP6 | Acute Toxicity

HP8 | Corrosive

HP10 | Toxic for reproduction

HP13 | Sensitising

HP14 | Ecotoxic

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

SECTION 14: Transport information
14.1 UN-Number

· ADR/RID/ADN, IMDG, IATA

UN2735

14.2 UN proper shipping name

· ADR/RID/ADN

2735 AMINES, LIQUID, CORROSIVE, N.O.S. (phenol, dodecyl-, branched, m-phenylenebis(methylamine)), ENVIRONMENTALLY HAZARDOUS

· IMDG, IATA

AMINES, LIQUID, CORROSIVE, N.O.S. (phenol, dodecyl-, branched, m-phenylenebis(methylamine))

(Contd. on page 9)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 58

Revision: 23.03.2021

Trade name: Epoxy LG filler hardener

(Contd. of page 8)

· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	
· Class	8 (C7) Corrosive substances.
· Label	8

· IMDG, IATA	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group	
· ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· Special marking (ADR/RID/ADN):	Symbol (fish and tree)
· 14.6 Special precautions for user	
· Hazard identification number (Kemler code):	Warning: Corrosive substances. 80
· EMS Number:	F-A,S-B
· Segregation groups	Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	
	Not applicable.
· Transport/Additional information:	

· ADR/RID/ADN	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	E

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (PHENOL, DODECYL-, BRANCHED, M-PHENYLENEBIS(METHYLAMINE)), 8, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 10)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 58

Revision: 23.03.2021

Trade name: Epoxy LG filler hardener

(Contd. of page 9)

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	8.6

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H361d Suspected of damaging the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

· Classification according to

Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Acute toxicity - oral
 Skin corrosion/irritation
 Serious eye damage/eye irritation
 Skin sensitisation
 Reproductive toxicity
 Hazardous to the aquatic environment - long-term (chronic)
 aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS:

Research and Development

· Contact:

Saïda El Asjadi, tel: +31 182 372177, e-mail: safety@de-ijsjel-coatings.nl

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 11)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 58

Revision: 23.03.2021

Trade name: Epoxy LG filler hardener

(Contd. of page 10)

Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Literature data and/or investigation reports are available through the manufacturer.

- Sources:
- * Data compared to the previous version altered.

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 51

Revision: 23.03.2021

*** SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1 Product identifier

Trade name: **Epoxy LG Filler base component**

Article number: 366
UFI: J9Q4-10JP-600X-V4V9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU19 Building and construction work
Product category PC9b Fillers, putties, plasters, modelling clay
Process category PROC19 Manual activities involving hand contact
Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article
ERC8c Widespread use leading to inclusion into/onto article (indoor)
ERC8f Widespread use leading to inclusion into/onto article (outdoor)
Article category AC13 Plastic articles
Application of the substance / the mixture See our technical datasheet for application details of this product.
Epoxy filler

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
Office hours: working days from 08:00 to 17:00 hrs.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 None

 GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

 GHS07



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

 
GHS07 GHS09

Signal word Warning

Hazard-determining components of labelling:

reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)

bis[4-(2,3-epoxypropoxy)phenyl]propane
1,6-bis(2,3-epoxypropoxy)hexane

Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P261 Avoid breathing mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection / face protection.

(Contd. on page 2)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 51

Revision: 23.03.2021

Trade name: Epoxy LG Filler base component

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**· 3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40	reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	25 – 50%
CAS: 933999-84-9 EC number: 618-939-5 Reg.nr.: 01-2119463471-41	1,6-bis(2,3-epoxypropoxy)hexane ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10 – 25%
CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2 Reg.nr.: 01-2119456619-26	bis[4-(2,3-epoxypropoxy)phenyl]propane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C \geq 5 % Skin Irrit. 2; H315: C \geq 5 %	2.5 – 10%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide ⚠ Carc. 2, H351	0.1 – 0.5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media**

- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

· 5.3 Advice for firefighters

- Protective equipment: No special measures required.

SECTION 6: Accidental release measures**· 6.1 Personal precautions, protective equipment and emergency procedures**

Not required.

(Contd. on page 3)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 51

Revision: 23.03.2021

Trade name: Epoxy LG Filler base component

(Contd. of page 2)

- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection: No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: Keep container tightly sealed.
 - Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- Additional information about design of technical facilities: No further data; see item 7.
- Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNEL (Derived No Effect Level) for workers		
9003-36-5 reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)		
Dermal	Acute - local effects, worker	8.3 µg/cm ² (Worker)
	Long-term - systemic effects, worker	104.15 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	29.39 mg/m ³ (Worker)
933999-84-9 1,6-bis(2,3-epoxypropoxy)hexane		
Dermal	Long-term - systemic effects, worker	2.8 mg/kg bw/day (Worker)
	Long term - local effects, worker	22.6 µg/cm ² (Worker)
Inhalative	Long-term - systemic effects, worker	10.57 mg/m ³ (Worker)
	Long-term - local effects, worker	0.44 mg/m ³ (Worker)
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Dermal	Long-term - systemic effects, worker	0.75 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	4.93 mg/m ³ (Worker)
13463-67-7 titanium dioxide		
Inhalative	Long-term - local effects, worker	10 mg/m ³ (Worker)
· DNEL (Derived No Effect Level) for the general population		
9003-36-5 reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)		
Oral	Long-term - systemic effects, general population	6.25 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	62.5 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	8.7 mg/m ³ (General population)

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 23.03.2021

Version number 51

Revision: 23.03.2021

Trade name: Epoxy LG Filler base component

(Contd. of page 3)

933999-84-9 1,6-bis(2,3-epoxypropoxy)hexane		
Oral	Acute - systemic effects, general population	0.83 mg/kg bw/day (General population)
	Long-term - systemic effects, general population	0.83 mg/kg bw/day (General population)
Dermal	Acute - systemic effects, general population	1.7 mg/kg bw/day (General population)
	Acute - local effects, general population	13.6 µg/cm ² (General population)
	Long-term - systemic effects, general population	1.7 mg/kg bw/day (General population)
Inhalative	Long-term - local effects, general population	13.6 µg/cm ² (General population)
	Acute - systemic effects, general population	2.9 mg/m ³ (General population)
	Long-term - systemic effects, general population	2.9 mg/m ³ (General population)
	Long-term - local effects, general population	0.27 mg/m ³ (General population)
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Oral	Long-term - systemic effects, general population	0.5 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	0.0893 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	0.87 mg/m ³ (General population)
13463-67-7 titanium dioxide		
Oral	Long-term - systemic effects, general population	700 mg/kg bw/day (General population)
· PNEC (Predicted No Effect Concentration) values		
9003-36-5 reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)		
Aquatic compartment - freshwater		0.003 mg/l (Freshwater)
Aquatic compartment - marine water		0.0003 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		0.0254 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater		0.294 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.0294 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		0.237 mg/kg dw (Soil)
Sewage treatment plant		10 mg/l (stp)
933999-84-9 1,6-bis(2,3-epoxypropoxy)hexane		
Aquatic compartment - freshwater		0.0115 mg/l (Freshwater)
Aquatic compartment - marine water		0.0015 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		0.115 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater		0.283 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.283 mg/kg sed dw (Sediment marine water)
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Aquatic compartment - freshwater		0.006 mg/l (Freshwater)
Aquatic compartment - marine water		0.001 mg/l (Marine water)
Aquatic compartment - sediment in freshwater		0.341 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		0.034 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		0.065 mg/kg dw (Soil)
Sewage treatment plant		10 mg/l (stp)
Oral secondary poisoning		11 mg/kg food (Food sec poisoning)
13463-67-7 titanium dioxide		
Aquatic compartment - freshwater		0.127 mg/l (Freshwater)
Aquatic compartment - marine water		1 mg/l (Marine water)
Aquatic compartment - water, intermittent releases		0.61 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater		1000 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water		100 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil		100 mg/kg dw (Soil)
Oral secondary poisoning		1667 mg/kg food (Food sec poisoning)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

· Personal protective equipment:
· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

(Contd. on page 5)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 51

Revision: 23.03.2021

Trade name: Epoxy LG Filler base component

(Contd. of page 4)

- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands: Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves: Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Recommended thickness of the material: ≥ 0.3 mm
- Penetration time of glove material: The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
- For the permanent contact gloves made of the following materials are suitable: Nitrile rubber, NBR
- As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
- Not suitable are gloves made of the following materials: Leather gloves
Strong material gloves
- Eye protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value at 20 °C:	7
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
· Flash point:	151 °C (Pensky Martens, ASTM D93)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	0 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	0.0 Vol %
Upper:	0.0 Vol %
· Vapour pressure:	Not determined.
· Density at 20 °C:	0.908 g/cm ³ (DIN 51757, ASTM D 1298)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.

(Contd. on page 6)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 51

Revision: 23.03.2021

Trade name: Epoxy LG Filler base component

(Contd. of page 5)

· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content: VOC (2004/42/EC):	0.00 %
Solids content:	100.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

· Components	Type	Value	Species
9003-36-5 reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)			
Oral	LD50	23800 mg/kg (Rat)	
Dermal	LD50	> 2000 mg/kg (Rabbit)	
933999-84-9 1,6-bis(2,3-epoxypropoxy)hexane			
Oral	LD50	2900 mg/kg (Rat)	
Dermal	LD50	> 4900 mg/kg (Rat)	
13463-67-7 titanium dioxide			
Oral	LD50	> 20000 mg/kg (Rat)	
Dermal	LD50	> 10000 mg/kg (Rabbit)	

- Primary irritant effect:
- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 7)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 51

Revision: 23.03.2021

Trade name: Epoxy LG Filler base component

(Contd. of page 6)

- Ecotoxicological effects:
- Remark: Toxic for fish
- Additional ecological information:
- General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP4	Irritant - skin irritation and eye damage
HP13	Sensitising
HP14	Ecotoxic

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number	
· ADR/RID/ADN, IMDG, IATA	UN3082
· 14.2 UN proper shipping name	
· ADR/RID/ADN	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)), MARINE POLLUTANT
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), reaction product: bisphenol-F-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN	9 (M6) Miscellaneous dangerous substances and articles. 9
· Class	
· Label	

· IMDG, IATA	9 Miscellaneous dangerous substances and articles. 9
· Class	
· Label	

(Contd. on page 8)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 51

Revision: 23.03.2021

Trade name: Epoxy LG Filler base component

(Contd. of page 7)

<ul style="list-style-type: none"> · 14.4 Packing group · ADR/RID/ADN, IMDG, IATA 	<p>III</p>
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR/RID/ADN): · Special marking (IATA): 	<p>Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)</p> <p>Yes</p> <p>Symbol (fish and tree)</p> <p>Symbol (fish and tree)</p> <p>Symbol (fish and tree)</p>
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	<p>Warning: Miscellaneous dangerous substances and articles.</p> <p>90</p> <p>F-A,S-F</p> <p>A</p>
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	<p>Not applicable.</p>
<p>· Transport/Additional information:</p>	
<ul style="list-style-type: none"> · ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code 	<p>5L</p> <p>Code: E1</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 1000 ml</p> <p>3</p> <p>E</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L</p> <p>Code: E1</p> <p>Maximum net quantity per inner packaging: 30 ml</p> <p>Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · UN "Model Regulation": 	<p>UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700), REACTION PRODUCT: BISPHENOL-F-(EPICHLORHYDRIN) EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700)), 9, III</p>

SECTION 15: Regulatory information

<ul style="list-style-type: none"> · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Directive 2012/18/EU · Named dangerous substances - ANNEX I · Seveso category · Qualifying quantity (tonnes) for the application of lower-tier requirements · Qualifying quantity (tonnes) for the application of upper-tier requirements · REGULATION (EC) No 1907/2006 ANNEX XVII 	<p>None of the ingredients is listed.</p> <p>E2 Hazardous to the Aquatic Environment</p> <p>200 t</p> <p>500 t</p> <p>Conditions of restriction: 3</p>
<p>· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II</p>	
<p>None of the ingredients is listed.</p>	
<p>· REGULATION (EU) 2019/1148</p>	
<p>· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))</p>	
<p>None of the ingredients is listed.</p>	
<p>· Annex II - REPORTABLE EXPLOSIVES PRECURSORS</p>	
<p>None of the ingredients is listed.</p>	

(Contd. on page 9)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 23.03.2021

Version number 51

Revision: 23.03.2021

Trade name: Epoxy LG Filler base component

(Contd. of page 8)

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Skin corrosion/irritation Serious eye damage/eye irritation Skin sensitisation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
---	--

· Department issuing SDS:

Research and Development

· Contact:

Saïda El Asjadi, tel: +31 182 372177, e-mail: safety@de-ijsse-coatings.nl

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Carc. 2: Carcinogenicity – Category 2
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
 Literature data and/or investigation reports are available through the manufacturer.

· Sources:

· * Data compared to the previous version altered.