

08.04.2022

Kit components

Product code	Description
--------------	-------------

422	Double Coat Modellak set
------------	---------------------------------

Components:

420	Double Coat Modellak basis
-----	----------------------------

421	Double Coat Modellak verharder
-----	--------------------------------

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Double Coat Modellak basis**

Article number: 420

UFI: 3KU4-C02H-H00P-X70H

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU19 Building and construction work

Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC19 Manual activities involving hand contact

PROC7 Industrial spraying

PROC11 Non industrial spraying

Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

Article category AC13 Plastic articles

AC7 Metal articles

AC11 Wood articles

Application of the substance / the mixture See our technical datasheet for application details of this product.
 Polyurethane lacquer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
 Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
 Office hours: working days from 08:00 to 17:00 hrs.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

 GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

 GHS07



STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

 
 GHS02 GHS07

Signal word Warning

Hazard-determining components of labelling:

2-methoxy-1-methylethyl acetate

Hazard statements H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 08.04.2022

Version number 36

Revision: 08.04.2022

Trade name: Double Coat Modellak basis

(Contd. of page 1)

- Additional information: EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- **2.3 Other hazards**
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	25 – 50%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide ⚠ Carc. 2, H351	25 – 50%
EC number: 905-588-0 Reg.nr.: 01-2119488216-32	Reactiemassa van ethylbenzeen en xyleen ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	2.5 – 10%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing agents: CO2 or powder. Fight larger fires with alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

- Protective equipment: No special measures required.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 3)

Trade name: Double Coat Modellak basis

(Contd. of page 2)

- **6.4 Reference to other sections** See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
 - Ensure good ventilation/exhaustion at the workplace.
 - Prevent formation of aerosols.
- Information about fire - and explosion protection:
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions: Keep container tightly sealed.
 - Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:		
108-65-6 2-methoxy-1-methylethyl acetate		
IOELV	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin	
· DNEL (Derived No Effect Level) for workers		
108-65-6 2-methoxy-1-methylethyl acetate		
Dermal	Long-term - systemic effects, worker	153.5 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	275 mg/m ³ (Worker)
13463-67-7 titanium dioxide		
Inhalative	Long-term - local effects, worker	10 mg/m ³ (Worker)
Reactiemassa van ethylbenzeen en xyleen		
Dermal	Long-term - systemic effects, worker	180 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, worker	77 mg/m ³ (Worker)
· DNEL (Derived No Effect Level) for the general population		
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	Long-term - systemic effects, general population	1.67 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	54.8 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, general population	33 mg/m ³ (General population)
13463-67-7 titanium dioxide		
Oral	Long-term - systemic effects, general population	700 mg/kg bw/day (General population)
Reactiemassa van ethylbenzeen en xyleen		
Oral	Long-term - systemic effects, general population	1.6 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	108 mg/kg bw/day (General population)
Inhalative	Acute - local effects, general population	289 mg/m ³ (Worker)
	Long-term - systemic effects, general population	14.8 mg/m ³ (General population)
· PNEC (Predicted No Effect Concentration) values		
108-65-6 2-methoxy-1-methylethyl acetate		
Aquatic compartment - freshwater		0.635 mg/l (Freshwater)

(Contd. on page 4)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 08.04.2022

Version number 36

Revision: 08.04.2022

Trade name: Double Coat Modellak basis

(Contd. of page 3)

Aquatic compartment - marine water	0.0635 mg/l (Marine water)
Aquatic compartment - water, intermittent releases	6.35 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	3.29 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	0.329 mg/kg sed dw (Marine water)
Terrestrial compartment - soil	0.29 mg/kg dw (Soil)
Sewage treatment plant	100 mg/l (stp)
13463-67-7 titanium dioxide	
Aquatic compartment - freshwater	0.127 mg/l (Freshwater)
Aquatic compartment - marine water	1 mg/l (Marine water)
Aquatic compartment - water, intermittent releases	0.61 mg/l (Intermittent release water)
Aquatic compartment - sediment in freshwater	1,000 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	100 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	100 mg/kg dw (Soil)
Oral secondary poisoning	1,667 mg/kg food (Food sec poisoning)
Reactiemassa van ethylbenzeen en xyleen	
Aquatic compartment - freshwater	0.327 mg/l (Freshwater)
Aquatic compartment - marine water	0.327 mg/l (Marine water)
Aquatic compartment - sediment in freshwater	12.46 mg/kg sed dw (Sediment freshwater)
Aquatic compartment - sediment in marine water	12.46 mg/kg sed dw (Sediment marine water)
Terrestrial compartment - soil	2.31 mg/kg dw (Soil)
Sewage treatment plant	6.58 mg/l (stp)

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.3 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

· For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

· As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

· Not suitable are gloves made of the following materials:

Leather gloves

Strong material gloves

· Eye protection:

Tightly sealed goggles

(Contd. on page 5)

Trade name: Double Coat Modellak basis

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value at 20 °C:	7
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	137 °C
· Flash point:	32 °C (Pensky Martens, ASTM D93)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	315 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.8 Vol %
· Vapour pressure at 20 °C:	3.4 hPa
· Density at 20 °C:	1.371 g/cm ³ (DIN 51757, ASTM D 1298)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	170 mPas (Brookfield, ASTM D1544)
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	29.3 %
VOC (2004/42/EC):	29.29 %
Solids content:	63.1 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition products:	No dangerous decomposition products known.

(Contd. on page 6)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 08.04.2022

Version number 36

Revision: 08.04.2022

Trade name: Double Coat Modellak basis

(Contd. of page 5)

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
ATE (Acute Toxicity Estimates)			
Dermal	LD50	14,818 mg/kg	
108-65-6 2-methoxy-1-methylethyl acetate			
Oral	LD50	8,532 mg/kg	(Rat)
13463-67-7 titanium dioxide			
Oral	LD50	> 20,000 mg/kg	(Rat)
Dermal	LD50	> 10,000 mg/kg	(Rabbit)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**

- Aquatic toxicity: No further relevant information available.

Type of test	Effective concentration	Method	Assessment
ATE (Acute Toxicity Estimates)			
Inhalative	LC50/4 h	148 mg/l	
108-65-6 2-methoxy-1-methylethyl acetate			
Inhalative	LC50/4 h	35.7 mg/l	(Rat)

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable

(Contd. on page 7)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 08.04.2022

Version number 36

Revision: 08.04.2022

Trade name: Double Coat Modellak basis

(Contd. of page 6)

HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP7	Carcinogenic

· Uncleaned packaging:

· Recommendation:

Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR/RID/ADN · IMDG, IATA	1263 PAINT PAINT
· 14.3 Transport hazard class(es) · ADR/RID/ADN · Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA · Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	III
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 30 F-E,S-E A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information: · ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code · Remarks:	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 D/E In packsize up to 450 liter exempt from ADR according ADR 2.2.3.1.5.
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ) · Remarks:	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml In packaging up to 30 litres exempt according to IMDG 2.3.2.5.
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I

None of the ingredients is listed.

· Seveso category

P5c FLAMMABLE LIQUIDS

(Contd. on page 8)

— EU —

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 08.04.2022

Version number 36

Revision: 08.04.2022

Trade name: Double Coat Modellak basis

(Contd. of page 7)

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	29.3

· **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H226 Flammable liquid and vapour.
 - H304 May be fatal if swallowed and enters airways.
 - H312 Harmful in contact with skin.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H351 Suspected of causing cancer.
 - H373 May cause damage to organs through prolonged or repeated exposure.
 - H412 Harmful to aquatic life with long lasting effects.

· Classification according to

Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	On basis of test data
Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS:

Research and Development

· Contact:

Saïda El Asjadi, tel: +31 182 372177, e-mail: safety@de-ijssel-coatings.nl

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

(Contd. on page 9)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 08.04.2022

Version number 36

Revision: 08.04.2022

Trade name: Double Coat Modellak basis

(Contd. of page 8)

PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Literature data and/or investigation reports are available through the manufacturer.

- Sources:
- * Data compared to the previous version altered.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Double Coat Modellak verharder**

Article number: 421
 UFI: U8K4-8040-T00P-S3G8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 SU19 Building and construction work
 Product category PC9a Coatings and paints, thinners, paint removers
 Process category PROC19 Manual activities involving hand contact
 PROC7 Industrial spraying
 PROC11 Non industrial spraying
 Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article
 ERC8c Widespread use leading to inclusion into/onto article (indoor)
 ERC8f Widespread use leading to inclusion into/onto article (outdoor)
 Article category AC13 Plastic articles
 AC7 Metal articles
 AC11 Wood articles
 Application of the substance / the mixture See our technical datasheet for application details of this product.
 Isocyanate hardener for polyurethanes

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
 Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl

Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
 Office hours: working days from 08:00 to 17:00 hrs.


SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

 GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

 GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

 GHS07

Acute Tox. 4 H332 Harmful if inhaled.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

  
 GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labelling:

aromatisch polyisocyanaat
 ethyl acetate
 m-tolylidene diisocyanate

Hazard statements

H225 Highly flammable liquid and vapour.
 H332 Harmful if inhaled.
 H319 Causes serious eye irritation.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.04.2022

Version number 37

Revision: 08.04.2022

Trade name: Double Coat Modellak verharder

(Contd. of page 1)

<ul style="list-style-type: none"> · Precautionary statements · Additional information: · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: · vPvB: 	<p>H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist/vapours/spray. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p> <p>EUH204 Contains isocyanates. May produce an allergic reaction.</p> <p>Not applicable. Not applicable.</p>
--	--

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures**

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 53317-61-6 NLP: 500-120-8	aromatisch polyisocyaanat ⚠ Eye Irrit. 2, H319; Skin Sens. 1, H317	50 – 100%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	10 – 25%
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34	m-tolylidene diisocyanate ⚠ Acute Tox. 1, H330; ⚠ Resp. Sens. 1, H334; Carc. 2, H351; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	0.1 – 0.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

<ul style="list-style-type: none"> · General information: · After inhalation: · After skin contact: · After eye contact: · After swallowing: · 4.2 Most important symptoms and effects, both acute and delayed · 4.3 Indication of any immediate medical attention and special treatment needed 	<p>Immediately remove any clothing soiled by the product. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.</p> <p>Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.</p> <p>Immediately wash with water and soap and rinse thoroughly. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.</p> <p>If symptoms persist consult doctor.</p> <p>No further relevant information available.</p> <p>No further relevant information available.</p>
--	--

SECTION 5: Firefighting measures**5.1 Extinguishing media**

· Suitable extinguishing agents: CO2 or powder. Fight larger fires with alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3)

Trade name: Double Coat Modellak verharder

(Contd. of page 2)

- **5.3 Advice for firefighters**
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to item 13.
 Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
- Information about fire - and explosion protection: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage: Store in a cool location.
- Requirements to be met by storerooms and receptacles: Not required.
- Information about storage in one common storage facility: Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- Further information about storage conditions: Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:		
141-78-6 ethyl acetate		
IOELV	Short-term value: 1468 mg/m ³ , 400 ppm Long-term value: 734 mg/m ³ , 200 ppm	
· DNEL (Derived No Effect Level) for workers		
141-78-6 ethyl acetate		
Dermal	Long-term - systemic effects, worker	63 mg/kg bw/day (Worker)
Inhalative	Acute - systemic effects, worker	1,468 mg/m ³ (Worker)
	Acute - local effects, worker	1,468 mg/m ³ (Worker)
	Long-term - systemic effects, worker	34 mg/m ³ (Worker)
	Long-term - local effects, worker	734 mg/m ³ (Worker)
26471-62-5 m-tolylidene diisocyanate		
Inhalative	Acute - systemic effects, worker	0.14 mg/m ³ (Worker)
	Acute - local effects, worker	0.14 mg/m ³ (Worker)
	Long-term - systemic effects, worker	0.035 mg/m ³ (Worker)
	Long-term - local effects, worker	0.035 mg/m ³ (Worker)

(Contd. on page 4)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 08.04.2022

Version number 37

Revision: 08.04.2022

Trade name: Double Coat Modellak verharder

(Contd. of page 3)

· DNEL (Derived No Effect Level) for the general population		
141-78-6 ethyl acetate		
Oral	Long-term - systemic effects, general population	4.5 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects, general population	37 mg/kg bw/day (General population)
Inhalative	Acute - systemic effects, general population	734 mg/m ³ (General population)
	Acute - local effects, general population	734 mg/m ³ (General population)
	Long-term - systemic effects, general population	367 mg/m ³ (General population)
	Long-term - local effects, general population	367 mg/m ³ (General population)

· PNEC (Predicted No Effect Concentration) values		
141-78-6 ethyl acetate		
Aquatic compartment - freshwater	0.26 mg/l (Freshwater)	
Aquatic compartment - marine water	0.026 mg/l (Marine water)	
Aquatic compartment - sediment in freshwater	0.34 mg/kg sed dw (Sediment freshwater)	
Aquatic compartment - sediment in marine water	0.034 mg/kg sed dw (Sediment marine water)	
Terrestrial compartment - soil	0.22 mg/kg dw (Soil)	
Sewage treatment plant	650 mg/l (stp)	

- Additional information: The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- Personal protective equipment:
- General protective and hygienic measures:
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes.
 - Avoid contact with the eyes and skin.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands:
 - Protective gloves
 - The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 - Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves
 - Nitrile rubber, NBR
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
 - Recommended thickness of the material: ≥ 0.3 mm
- Penetration time of glove material
 - The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
- For the permanent contact gloves made of the following materials are suitable:
 - Nitrile rubber, NBR
- As protection from splashes gloves made of the following materials are suitable:
 - Nitrile rubber, NBR
- Not suitable are gloves made of the following materials:
 - Leather gloves
 - Strong material gloves
- Eye protection:
 - Tightly sealed goggles

(Contd. on page 5)

Trade name: Double Coat Modellak verharder

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value at 20 °C:	7
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	77 °C
· Flash point:	1 °C (Pensky Martens, ASTM D93)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	460 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	2.1 Vol %
Upper:	11.5 Vol %
· Vapour pressure at 20 °C:	97 hPa
· Density at 20 °C:	1.17 g/cm ³ (DIN 51757, ASTM D 1298)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic at 20 °C:	1,800 mPas (Brookfield, ASTM D1544)
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	25.0 %
VOC (2004/42/EC):	25.00 %
Solids content:	75.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity	No further relevant information available.
· 10.2 Chemical stability	
· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
· 10.3 Possibility of hazardous reactions	No dangerous reactions known.
· 10.4 Conditions to avoid	No further relevant information available.
· 10.5 Incompatible materials:	No further relevant information available.
· 10.6 Hazardous decomposition products:	No dangerous decomposition products known.

(Contd. on page 6)

Trade name: **Double Coat Modellak verharder**

(Contd. of page 5)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- Acute toxicity Harmful if inhaled.
- LD/LC50 values relevant for classification:

Components	Type	Value	Species
141-78-6 ethyl acetate			
Oral	LD50	5,620 mg/kg	(Rabbit)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.

Type of test	Effective concentration	Method	Assessment
ATE (Acute Toxicity Estimates)			
Inhalative	LC50/4 h	16.7 mg/l	
141-78-6 ethyl acetate			
Inhalative	LC50/4 h	1,600 mg/l	(Rat)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:
- General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP13	Sensitising

(Contd. on page 7)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 08.04.2022

Version number 37

Revision: 08.04.2022

Trade name: Double Coat Modellak verharder

(Contd. of page 6)

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

*** SECTION 14: Transport information**

· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR/RID/ADN · IMDG, IATA	1263 PAINT PAINT
· 14.3 Transport hazard class(es) · ADR/RID/ADN · Class · Label	3 (F1) Flammable liquids. 3
· IMDG, IATA · Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category	Warning: Flammable liquids. 33 F-E, <u>S</u> -E A
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information: · ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I
None of the ingredients is listed.
- Seveso category
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50,000 t

(Contd. on page 8)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 08.04.2022

Version number 37

Revision: 08.04.2022

Trade name: Double Coat Modellak verharder

(Contd. of page 7)

- REGULATION (EC) No 1907/2006
ANNEX XVII

Conditions of restriction: 3, 74

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- National regulations:

- Technical instructions (air):

Class	Share in %
I	0.3
NK	25.0

- **15.2 Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H225 Highly flammable liquid and vapour.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H330 Fatal if inhaled.
 - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H351 Suspected of causing cancer.
 - H412 Harmful to aquatic life with long lasting effects.

- Classification according to

Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Flammable liquids	On basis of test data
Acute toxicity - inhalation Serious eye damage/eye irritation Respiratory sensitisation Skin sensitisation Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- Department issuing SDS:

Research and Development

- Contact:

Saïda El Asjadi, tel: +31 182 372177, e-mail: safety@de-ijssel-coatings.nl

- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 9)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 08.04.2022

Version number 37

Revision: 08.04.2022

Trade name: Double Coat Modellak verharder

(Contd. of page 8)

vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 1: Acute toxicity – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Resp. Sens. 1: Respiratory sensitisation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
Literature data and/or investigation reports are available through the manufacturer.

- Sources:
- * Data compared to the previous version altered.